


Easily diversify your business with...

ZAP[®]

The **SAFEST** Sectional Door Opener in the World



804 with parts



Zap[™] DC Motor Drives

- Operates overhead, profile lift or vertical lift sliding sectional door types.
- **Requires only 110V single phase 3-5 Amp power supply** (8 Amps with lighting control).

Sensitive Obstruction Detection

- Door can be stopped by hand pressure during the close cycle.
- Fast variable speed operation with an automatic speed change point calibration just before each limit of door travel. This soft stop variable speed drive avoids cables jumping the drums.

Manual Override

- Manual override easily enables disengagement of the drive, to allow the door to be moved by hand.

Zap[™] Controllers

- Controller provides automatic stop and reopen control if the door meets an obstruction during the close cycle.
- Controller incorporates an adjustable auto-close timer and full safety control from photobeams etc.
- Does not require limit switches, as the controller monitors motor current, and automatically stops the door at each limit of travel.
- Controller will automatically stop the motor on sensing a slide lock left in the locked position. This is detected without an interlock switch, by motor current sensing.



805

- **Low voltage**
- **No limit switches**
- **Avoids cables jumping**
- **One man quick installation**
- **Compact, lightweight & powerful**



8804

Copyright: Zap Controls UK

Model	Maximum Door Size	Door Height		Door Weight
		Minimum	Maximum	
804 805	170 sq. ft.	6' 6"	33' 0"	775 lbs.
8804 8805	350 sq. ft.	9' 6"	40' 0"	1600 lbs.

Commercial jobs have never been so easy!

ZAP[®]

The **SAFEST, SMALLEST,
FASTEST INSTALLING**

Jackshaft Operator



Low voltage DC motor
Compact, lightweight & powerful
Avoids cables jumping
No limit switches

One man quick installation

- Fast action **variable** speed, smooth drive & quiet operation
- Superb **safety** control
- Sensitive safety stop and reopen
- Stop & reopen C.E.N. safety control from photobeams etc.
- Requires **single phase 110V** power supply only
- Operates during power failure with optional battery pack
- Adjustable auto-close timer
- Traffic light control & interlock optional interface
- Field proven & time tested
- Approved for Commercial Use: CSA/UL325



Sensitive obstruction detection

